



Access Collection

Mannington
COMMERCIAL



Cover: Stone - Linear Stone Shale SX5S3606, **Abstract** - Linen Weave SX5A3800,
Wood - Shibori Jasmine SX5W7800
Above: Stone - Linear Stone Black SX5S2405



Stone - Linear Stone Shale SX5S3606







Wood - Shibori Jasmine SX5W7800



Wood - Black Walnut SX5W2534



Wood - Frosted Oak SX5W5020

Access Collection Product Availability

Product Name	Product Code	Surface Finish	Micro-beveled Edges	5.91" x 39.37" (150.1 x 1000 mm)	17.7" x 17.7" (449.6 x 499.6 mm)
ABSTRACT					
Equator Wave	SX5AEQ39	Ceramic	•		•
Linen Weave	SX5A3800	Ceramic	•		•
Urban Line Felt	SX5A3271	Ceramic	•		•

STONE					
Ceramic Dark	SX5S3566	Ceramic	•		•
Ceramic Ecu	SX5S3592	Ceramic	•		•
Ceramic Flint	SX5S2594	Ceramic	•		•
Ceramic Light	SX5S1565	Ceramic	•		•
Dry Stone Clay	SX5S4435	Ceramic	•		•
Linear Stone Black	SX5S2405	Ceramic	•		•
Linear Stone Shale	SX5S3606	Ceramic	•		•

WOOD					
Ashdown Plum	SX5W8000	Tick	•	•	
Black Walnut	SX5W2534	Tick	•	•	
Bleached Elm	SX5W2516	Tick	•	•	
Dusky Walnut	SX5W2542	Tick	•	•	
Frosted Oak	SX5W5020	Rustic	•	•	
Shadow Oak	SX5W5022	Rustic	•	•	
Shibori Jasmine	SX5W7800	Tick	•	•	
Simple Beech	SX5W5023	Tick	•	•	
Traditional Oak	SX5W2514	Tick	•	•	
Winter Oak	SX5W5021	Rustic	•	•	

Access Collection

Style	Wood	Stone & Abstract
Construction	Luxury Vinyl Tile Non-ortho Phthalate	Luxury Vinyl Tile Non-ortho Phthalate
Classification	ASTM F1700 Class III, Type B	ASTM F1700 Class III, Type B
Total Thickness	0.197" (5 mm)	0.197" (5 mm)
Wear Layer Thickness	20 mil (0.51 mm)	20 mil (0.51 mm)
Wear Layer	Enhanced Urethane	Enhanced Urethane
Edge Treatment	Micro-bevel	Micro-bevel
Sizes	5.91" x 39.37" (150.1 x 1000 mm) (nominal)	17.7" x 17.7" (449.6 mm x 449.6 mm)
Colors	10	7 - Stone, 3 - Abstract
Packaging	12 pcs, 19.375 ft ² (1.8 m ²), 36.19 lbs (16.42 kg)	10 pcs, 21.79 ft ² (2.024 m ²), 40.7 lbs (18.46 kg)
Adhesive	<p>Loose Lay with Perimeter Glue: Amtico Tackifier XpressStep for LVT & Sheet Vinyl Full Coverage Spray Porous & Non-porous Substrates - Fully Adhered, Releasable: Amtico Tackifier Porous & Non-porous Substrates - Fully Adhered, Permanent: Amtico 373 Full Spread, Acrylic Latex Amtico PSA Full Spread, Transitional Pressure Sensitive, High Moisture Amtico RP-18 Full Spread, One Component Non-porous Substrates: XpressStep for LVT & Sheet Vinyl Full Coverage Spray XpressStep Premium for LVT Full Coverage High Moisture Spray Note: Must use Amtico RP-18 or XpressStep adhesive under hospital beds and heavy rolling loads or where high performance is needed. Amtico RP-18 is required in areas with excessive heat or cold expectation and exposure to direct sunlight or in areas with topical water such as shower rooms.</p>	
Installation Method	<p>All arrows in the same direction. Planks should have end joints offset by at least 6" and staggered to create a random appearance. Tiles should be installed block or staggered; when quarter turned, arrows should alternate.</p>	
Testing		
HUD/FHA	Passes	
Flexibility (ASTM F137)	Passes - 1" Mandrel - No Crack/Break	
Dimensional Stability (ASTM F2199)	Passes - Max 0.020 in/lin ft	
Squareness (ASTM F540)	Passes - Max 0.010"	
Static Load (ASTM F970 mod.)	Passes - 2,000 PSI; Residual Indent ≤ 0.005"	
Residual Indentation (ASTM F1914)	Passes - < 8% Avg / 10% Single Value	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²	
Smoke Density (ASTM E662)	Passes - ≤ 450	
Slip Resistance (ASTM C1028)	Passes - ≥ 0.5 Leather; 0.6 Rubber	
Acoustic IIC (ASTM E492)	6" Concrete with Drop Ceiling	
Acoustic STC (ASTM E90)	6" Concrete with Drop Ceiling	
Resistance to Light (ASTM F1515)	Passes	
Chemical Resistance (ASTM F925)	Passes	
Resistance to Heat (ASTM F1514)	Passes	
Environmental Data		
Indoor Air Quality	FloorScore Certified; CDPH v1.1-2010	
Product Declarations	EPD	
LEED Scoreboard	<p>May contribute to LEED credits: LEED 2009: IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; IEQc2 - Low Emitting Materials</p>	
mindful Materials	Visit mM Origin website, mindfulmaterials.origin.build, for current transparency information	
Manufacturing	South Korea	
Warranty		
Limited 10 Year Commercial Warranty		