

Mannington Commercial Wayfinding LVT Products



Crafted with Purpose®

Mannington
COMMERCIAL

How Do I Order Mannington Wayfinding LVT Products?

Elevate your design with Mannington's Wayfinding LVT offering. Customizable in color and design with no minimum order quantity. Easy to use with existing LVT or new installations. Follow these easy steps to get started.

1 Choose your size

- 18" x 18" – square
- 18" x 18" – inset circle
- 4.5" x 36" – plank
- 7.25" x 48" – plank
- [Custom option available]

2 Choose your message

- Choose from 6 standard icons, 3 standard plank messages or create your custom message

3 Choose your background and foreground colors from the Pantone Matching System (PMS)

- Choose one background and one foreground PMS color from our color bank or let us help you choose the perfect color for your installation (limit 2 colors)
- [More than 2 color options available as custom]

[Download the Mannington PMS Color Bank](#)

Product Information

- Made in the USA
- 2.5 mm total thickness
- Quantum Guard Elite® Wear Layer & Warranty
- Ceramic Emboss
- Ordered by the piece
- Standard lead times

Don't see your message? We have custom options available. Call your local Mannington Commercial representative for more information.



Message 1




Message 2



Message 3




Message 4



Message 5



Message 6



Inset circle can be rotated to fit any required direction.







Practice Social Distancing



Mannington Commercial Wayfinding LVT

Style	Wayfinding LVT
Construction	Luxury Vinyl Tile Non-ortho Phthalate
Classification	ASTM F1700 Class III, Type B
Total Thickness	0.098" (2.5 mm)
Wear Layer	Quantum Guard Elite®
Edge Treatment	Micro-bevel or Unbeveled
Sizes	18" x 18" square 18" x 18" inset circle 4.5" x 36" plank 7.25" x 48" plank Custom options available
Colors	Pantone Matching System (PMS) colors available to choose from
Adhesive	Porous & Non-porous Substrates: Amtico PSA Full Spread, Transitional Pressure Sensitive, High Moisture Amtico RP-18 Full Spread, One Component XpressStep for LVT & Sheet Vinyl Full Coverage Spray XpressStep Premium for LVT Full Coverage High Moisture Spray Porous Substrates Only: Amtico 373 Full Spread Note: Must use Amtico RP-18, XpressStep or XpressStep Premium adhesive under hospital beds and heavy rolling load areas. Use Amtico RP-18 where higher risk of topical moisture would be a concern.
QuickStix®	Available with QuickStix® pre-applied adhesive, reducing time and labor required to install the flooring.
Installation Method	Please refer to Mannington Commercial Wayfinding LVT Installation Instructions
Testing	
HUD/FHA	Passes
Flexibility (ASTM F137)	Passes - 1" Mandrel - No Crack/Break
Dimensional Stability (ASTM F2199)	Passes - Max 0.020 in/in ft
Squareness (ASTM F540)	Passes - Max 0.010"
Static Load (ASTM F970 mod.)	Passes - 2,000 PSI; Residual Indent ≤ 0.005"
Residual Indentation (ASTM F1914)	Passes - < 8% Avg / 10% Single Value
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm2
Smoke Density (ASTM E662)	Passes - ≤ 450
Slip Resistance (ASTM C1028)	Passes - ≥ 0.5 Leather; 0.6 Rubber
Resistance to Light (ASTM F1515)	Passes
Chemical Resistance (ASTM F925)	Passes
Resistance to Heat (ASTM F1514)	Passes
Environmental Data	
Rapidly Renewable Content	Contains 3% rapidly renewable resource content
Indoor Air Quality	FloorScore Certified; CDPH v1.1-2010
Product Declarations	EPD, HPD
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRc5 Regional Materials; MRc6 Rapidly Renewable Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials
mindful MATERIALS Manufacturing	Visit mM Origin website, mindfulmaterials.origin.build , for current transparency information Madison, GA (USA) - ISO 14001 EMS & ISO 9001 QMS Registered
Warranty	
	Limited 25-Year Commercial Warranty Limited 25-Year Quantum Guard Elite® Wear Warranty

